

BelAir200 Wireless Multi-service Switch Router

The BelAir200 Wireless Multi-service Switch Router is the industry's highest performance and most flexible multi-radio node offering mobile broadband over Wi-Fi, WiMAX, Cellular, and 4.9 GHz Public Safety spectrums. The BelAir200 leverages a leading-edge modular design to deliver switched backhaul capabilities for greater network performance, lower latency, and resiliency via built in self-healing features. Offering true standards-based seamless mobility, the BelAir200 ensures that subscribers do not experience service interruptions to critical applications, like voice and video, as they move throughout the wireless mesh network.

Modular architecture

The BelAir200 modular architecture provides four radio slots that can contain any combination of Backhaul Radio Modules (BRMs), WiMAX Radio Modules (WRMs) and Access Radio Modules (ARMs) in the same wireless mesh node. The ARMs, WRMs, and BRMs support a broad range of Wi-Fi (IEEE 802.11a/b/g), WiMAX (IEEE 802.16d), 4.9 Public Safety and Cellular (via a T1/E1 Circuit Emulation Module) applications.

For large scale wireless mesh networks, the industry-leading BelAir200 provides the ideal flexibility and capacity in a multi-service solution.

Layer 2/3 networking capabilities

The BelAir200 has an integrated Layer 2/3 Switch Router engine that provides extensive QoS, VLAN, Network Security and Traffic Management capabilities that are necessary for transporting mission critical, time-sensitive applications like voice and video.



Features

- Modular multi-service multi-radio architecture
- Supports Wi-Fi, WiMAX and Cellular
- Seamless mobility for uninterrupted service
- Network Management via CLI, WEB or BelView NMS
- Electrical and optical Ethernet interface options
- Circuit Emulation Module (TDM Pseudowire)

Radio module options

- Access Radio Module (ARM)
IEEE 802.11a/b/g & 4.9 Public Safety
- Backhaul Radio Module (BRM)
IEEE 802.11a pre-WiMAX & 4.9 Public Safety
- WiMAX Radio Module (WRM)
IEEE 802.16d
- Radios available in multiple frequency bands
 - licensed: 2.3 GHz, 2.5 GHz and 4.9 GHz
 - unlicensed: 2.4 GHz and 5.25-5.85 GHz

Network Management

The BelAir200 can be managed via a Command Line Interface (CLI), WEB GUI or with BelAir Networks BelView Network Management System (NMS). Both CLI and WEB GUI provide device level support, and BelView NMS provides complete network-wide support for Fault, Configuration and Performance Management. BelView NMS works on either Windows XP or SUN Solaris platforms and can also be integrated into other management systems like HP OpenView or IBM NetView.

BelAir Networks is the leading provider of mobile broadband mesh networking solutions. Cities around the world rely on BelAir to deliver industry-leading broadband performance and scalability, and carrier-class capacity and reliability. BelAir Networks teams with world-class global partners to deploy proven, cost-effective wireless broadband mesh networks.

Networking

- 1-port 10/100BASE-TX (Cat. 5 RJ-45) Ethernet Interface
- 1-port 100BASE-FX (SMF) Ethernet Interface
- 4 x T1 (CEM) Interface
- IEEE 802.1D MAC Bridging
- IEEE 802.1Q VLANs
- IEEE 802.1w (RSTP) and IEEE 802.1s (MSTP)
- IEEE 802.1p prioritization with 4 queues
- Ingress/Egress Rate Limiting
- IPTOS Re-write
- IP Filtering
- Flow Accounting
- 16 SSIDs per access radio. MBSSID support for 8 virtual APs per access radio
- Support for SNMP, ICMP, HTTP, ARP, TCP, UDP, Telnet, TFTP and IP traffic

Management

- Secure local and remote access
- Command line, HTTP and HTTPS Web GUI, SNMPv1/v2/v3 and SSHv2 management interfaces
- MIBs: MIB-II, SNMPv2, 802.11, Ethernet-like, Interface Group, IP Forwarding Table, OSPFv2
- Multiple user privilege levels with RADIUS authentication
- Firmware upgrade through TFTP with support for automatic rollback
- RADIUS accounting

Security

- Authentication: 802.1x (RADIUS) and EAP methods
- Encryption: WEP 64 and 128 bit, TKIP / MIC per 802.1x, 802.11i AES
- MAC address access control lists
- Rogue AP detection

Approvals

- Radio: FCC part 15 and part 27, EN 300 328, EN 300 440, EN 301 893 and Industry Canada RSS 210 Issue 5
- EMC: FCC 47 CFR part 15, subpart B Class B and EN 301 489-1/-17 Class B
- Safety: ANSI/UL std no.60950-1, CSA-C22.2 std no. 60950-1, CB-60950-1
- Laser safety: Class 1 laser product complies with 21CFR 1040 and IEC60825
- RF safety: FCC OET Bulletin 65, Health Canada Safety code 6
- Outdoor use: IP56/NEMA4/NEMA4X for wet and dusty conditions
- CE! mark
- Mexico: NOM
- Korea: MIC2003-15
- Russia: GOST-R
- India: ETA-74/2005, ETA-78/2005
- Taiwan: LP00002, ETC094LP0425, ETC094LPD0426, ETC094LPD0426a

Physical and Electrical

- Size: 11.5 in. (29.2 cm) diameter x 16 in. (40.6 cm) high
- Weight: 28 lbs (12.7 kg)
- Typical power consumption: 58 Watts
- Power supply: 100 to 240 V ac, 47 to 63 Hz
- Backup 12V battery
- Battery backup time: 20 minutes typical
- Available wall or pole mounting kits with theft deterrent anti-tamper screws
- Power, radio and Ethernet lamps

Protection circuits

- IEC 60000-4-5 level 4 surge
- GRI089 - 6 kV (3000 A) surge

Environmental

- Operating temperature: -40°C to +50°C
- Storage temperature: -40°C to +80°C
- Operating humidity: 5 to 95% non-condensing
- Shock and vibration: ETSI300-019-1-4



Copyright© 2007 BelAir Networks. BelAir Networks products and associated technology are protected by one or more of the following US patents: 7,171,223 / 7,164,667 / 7,154,356 / 7,030,712 / D501,195. Specifications may vary by region.

To find out more, contact BelAir Networks:

info@belairnetworks.com

sales@belairnetworks.com

1-877-BelAir1 (1-877-235-2471)

1-613-254-7070

www.belairnetworks.com

BDMA20020-B02